

398.00 EUR
 incl. 19% VAT, plus [shipping](#)

- FANLESS carpc system
- Core2Duo
- Dualchannel VGA
- Intel 945 chipset



CARTFT.COM



Support: [Assembling Tutorial \[DE\]](#) | [Assembling Tutorial \[EN\]](#)

Fanless CarPC-barebone for use with Intel Celeron M440 CPU.

CALU specifications	
Processor (supported)	Support Socket 479, FSB 533MHZ, FSB 667MHZ, Intel Mobil CPU (Celeron M 410, 420, 430, 440 & 450 CPU, Core Duo T2300, T2400, T2500, T2600 & T2700 CPU, Core 2 Duo T5500, T5600, T7200, T7400 & T7600 CPU).
Memory	Support 1x SO-DDR-II RAM
Chipset	Intel Intel 945GM / ICH 7M
Video	Intel Graphics Media Accelerator 950
Audio	Software AC '97 Audio CODEC

Peripheral Connection	Front : 1 x IEEE 1394 Firewire port 1 x USB 2.0 / 1.1 Port 1 x MIC Port 1 x Ear Phone output Jack Power-on button Reset button Power-on and HDD LED Rear : 1 x RS232 COM port 1 x RJ45 10/100/1000 Mbit Fast Ethernet 1 x Line-Out output Jack 2 x USB 2.0 / 1.1 Ports 1 x 15 pin VGA 1 x DVI 1 x TV-Out 1 x 12v DC Power Jack input
Storage	One 2.5 inch SATA Hard Disk (Support Ultra DMA 33/66/100).
Weight & Size	System approximately 3kg (fully equipped). System Dimension: 155 x 255 x 55 mm
Power req.	12V, 5A
Accessory	
Storage	Supports all Standard Slim CD-ROM/DVD-ROM, CD-RW, DVD-RW Combo Supports all 2.5" SATA IDE hard drive, ATA-100/66/33.
Scope of supply	110V/230V EU power supply Barebone CPU Kühlkörper

Graphics driver for 800x480 resolution : [Here](#)