



379.00 EUR
 incl. 19% VAT, plus [shipping](#)

- JBC311U93W-2930-B



- INTEL® Bay Trail-M N2930 SoC Processor 1.83GHz, Quad-Core, 7.5W
- Embedded Long-life Series, 5 Year Availability
- NUC Form Factor (101mm X 101mm) Design for Fanless Systems
- 9V~24V DC jack on back panel for external power supply
- 2 x HDMI & 2 x LAN
- ECO-design for EuP/ErP

Model No	JBC311U93-2930-B JBC311U93-2930-S	JBC311U93W-2930-B JBC311U93W-2930-S
Part No	HBJC311U93-2930-B HBJC311U93-2930-S	HBJC311U93W-2930-B HBJC311U93W-2930-S
Motherboard Specification		
CPU	Fanless INTEL® Bay Trail-M Celeron N2930 SoC Processor 1.83GHz, Quad-Core, 7.5W	
Memory	1 * 204-pin DDR3L-1333 SO-DIMM Single Channel up to 8 GB (1.35V required)	
VGA	Intel® HD Graphics	

LAN	2 x Intel® 82583V Gigabit Ethernet	
Audio	Realtek ALC887 Audio CODEC with SPDIF out	
Storage	1 x full size mSATA Slot	
Wireless / Mini-PCIE Slot	1 x half size Mini-PCI Express Slot	Wireless 802.11 b/g/n + Bluetooth 4.0
Board Form Factor	NUC Form Factor (101mm X 101mm)	
Chassis Specification		
Product size	116 * 110 * 49 mm	
Material	Lightweight aluminum alloy with extruded aluminum IO panel	
Color	Black and Silver	
HDD	NA	
Front I/O Port	1 * Power Button 1 * Power LED 1 * RS232/422/485 COM port 1 * USB 3.0 1 * USB 2.0	
Rear I/O Port	2 * USB 2.0 ports 2 * HDMI 2 * RJ-45 port 1 * Audio line out with SPDIF out 1 * 9V ~ 24V DC-in jack 2 * SMA Connector for WiFi Antenna 1 * Kensington Lock Hole	
Power	Adapter : AC_90~240V / DC_12V_3A/36W	
Environment	Operating Temperature : 0°C ~ 40°C with air flow Storage Temperature : -20°C ~ 80°C	
Standard Accessory	✓ 36W AC Adapter x1 ✓ Power Cord x1 ✓ Screw pack x1 ✓ DVD Disk x1 ✓ Manual x1 ✓ WALL + VESA + DIN rail mounting kit (Black) ✓ Din Rail Clip ✓ WIFI antenna (with HBJC311U93W-2930 model)	
Functional	Digital Signage, Set Top Box, Thin Client, Car Entertainment, Smart Mini PC, POS/POI, KIOSK, HTPC	
Certificate	CE,FCC,ErP For Barebone CE,FCC,TUV,UL,CCC,CB,ErP For Power Adapter	