

819.00 EUR
 incl. 19% VAT, plus [shipping](#)



- M/B Model: NF9HG-2930
- INTEL® Bay Trail-M/D/I Processor Processor
- 2 * SO-DIMM slot (Max to 8GB)
- 1 * full size Mini PCI-E slot for m-SATA Device
- 1 x mini-PCIe(Full Size), 1 x mSATA(Full Size),
- 2 x PCIe1
- 2 * 2.5" SATA HDD
- Application: Networking, POE, Surveillance

• Product Dimension	• 430 (W) * 251 (D) * 43 (H) mm
• Product Model	• JBC153F9HG-2930-B • JBC153F9HG-2930G2 • JBC153F9HG-2930G4
• MB Model & Size	• JNF9HG-2930 / MINI-ITX
• BIOS	• AMI 64Mb Flash ROM
• CPU	• INTEL® Bay Trail – M/D/I Processor (2930)
• Memory	• SO-DIMM DDR3L 1333/1066MHz * 2 (Max 8GB)
• Storage	• 2.5" SATA HDD * 2
• Expansion	• Full size Mini-PCIE * 2 (Support M-SATA*1) • SIM Card Slot * 1 • Support TPM (option) • 2 x PCIe1
• FAN	• DC-12V / 4020 FAN * 3

• Front I/O Port	<ul style="list-style-type: none"> • Power LED * 1 , HDD LED * 1 • COM * 2 , GPIO * 1 • VGA * 1 • USB 3.0 * 1 , USB 2.0 * 1 • Giga LAN (Intel i211AT) * 4 • Expansion 2 ports LAN PCI-E Card (JBC153F9HG-2930G2) • Expansion 4 ports LAN PCI-E Card (JBC153F9HG-2930G4)
• Rear I/O Port	<ul style="list-style-type: none"> • AC input * 1 • PW SW * 1
• Power Source	<ul style="list-style-type: none"> • 1U 200W FLEX POWER • AC 90~240V input
• Accessory	<ul style="list-style-type: none"> • AC Cable * 1 , Screw Package * 1 • User Manual * 1 , CD * 1
• Packing	<ul style="list-style-type: none"> • Net Weight ■4.2KG • Gross Weight ■5KG • Color Box Dimension ■560 (W) x 400 (D) x 380 (H) mm
• Temperature	<ul style="list-style-type: none"> • Operating within 0~60 centigrade • Storage within -10~70 centigrade
• Certification	<ul style="list-style-type: none"> • EMC : CE , FCC • Safety : RoHS , ErP
• Applications	<ul style="list-style-type: none"> • Networking • Surveillance