

689.00 EUR
 incl. 19% VAT, plus [shipping](#)



- Intel 10/11th Gen. Socket !
- LGA1200 !
- HBFFI02 !



- Intel LGA1200 Socket 10/11th generation Pentium, Core i3, i5, i7 Processors, up to 35W
- Dual CH non-ECC DDR4 2933/2666/2400MHz SODIMM
- 1* 2.5" HDD TRAY Design
- Support 2* HDMI, 1* DP, 4* COM, 2* USB2.0, 4* USB 3.2, 1* Line-out, 1* MIC
- Adapter DC19V 120W

| | | | |
|----------------|--|--------------------------|---|
| MB Model | – MI02-Q470 Series/ Mini-ITX | | |
| Part No | Non-Wifi | M.2 ac WiFi card | TPM2.0 |
| | – HBFFI02-Q470-B | – HBFFI02I-Q470-B (WIFI) | – HBFFI02-Q470- T (non-WIFI + TPM2.0) – HBFFI02I-Q470- T (WIFI + TPM2.0) |
| BIOS | – AMI Flash ROM | | |
| CPU/Chipset | – INTEL® LGA 1200 Socket 10/11th generation Core i7 / i5 / i3 /Pentium CPU (35W) – INTEL® Q470E chipset Notes : When the system runs, CPU will automatically adjust its working clock frequency according to changing workload. | | |
| Memory | – 2 * SO-DIMM slots / dual channel DDR4 2933/2666/2400MHz up to 64GB * Core i9 / i7 CPUs support DDR4 up to 2933MHz * Core i5 / i3 CPUs support DDR4 up to 2666MHz * Pentium / Celeron CPUs support DDR4 up to 2400MHz | | |
| Network | – 1 * Intel i219LM GbE – 1 * Intel i225LM 2.5GbE | | |
| Storage | – 1 * 2.5" SATAIII 6Gb/s internal drive bay (only support 2.5" HDD with a height ≤ 10mm) – 1 * M.2 M-Key 2280 (SATA/PCIex4) support NVMe | | |
| Expansion slot | – 1 * M.2 E-Key, 2230 (PCIe x1 /USB2.0) support CNVi – 1 * M.2 B-Key 3042/3052 (USB3.0/USB2.0/PCIe x1) W/SIM card holder | | |

| | |
|-----------------|--|
| Rear Panel I/O | <ul style="list-style-type: none"> - 4 * USB 3.2 - 2 * HDMI (Max Resolution: 4096x2160@30Hz) - 1 * DP (Max Resolution: 4096x2304@60Hz) - 2 * RJ45 - 1 * Line-out, 1 * MIC - 4 * COM - 1 * DC-in |
| Front Panel I/O | <ul style="list-style-type: none"> - 1 * Power button, 1 * Power LED, 1 * HDD LED - 2 * USB 2.0 - 1 * 2.5" HDD Tray (Easy to replace the hard disk, does not support hot swap) |
| Compliance | - CE, FCC, LVD, RoHS, ErP Ready |
| Power Source | <ul style="list-style-type: none"> - MB : DC12~28V input - Adapter : AC110~240V to DC19V-6.3A 120W |
| Temperature | <ul style="list-style-type: none"> - Operating Temperature: -20 ~ 50° C (The test environment is closed and windless) - Storage Temperature: -10 ~ 70° C - Humidity: 90% , non-condensing |
| Dimensions | - 290 (W) x 207 (D) x 65 (H) mm |
| Packing | <ul style="list-style-type: none"> - Net Weight: 3.8KG - Gross Weight: 4.8KG - Color Box dimension: 406 (W) * 148 (D) * 359 (H) mm |
| OS Support | - Windows 10, Linux |